



Shenzhen eybond co ltd Czechia

NEMonitor System, based on the back-end server products of Eybond IOT cloud, provides users with application services such as data collection, analysis, calculation, storage, alarm push, peak cutting and valley filling, energy-saving strategy, etc. of energy storage device through cloud computing, big data, intelligent sensor and other advanced ...

MagicBox Pro is one of the key device to build a centralized control center. It collects data of local device through RS-485, or obtains data of cloud server through Ethernet (RJ-45), Wi-Fi and 4G, and displays monitoring data through display, projector, splicing screen, etc.

RTU series industrial series datalogger can support communication modes such as Wi-Fi, GPRS, 4G and Ethernet, and collect device data through multiple interfaces such as RS-485 and RS-232 has low requirements for the hardware interface and transmission environment of the device, and is perfectly compatible with inverter, energy storage machine, environmental ...

Stick series pluggable datalogger can support GPRS and Wi-Fi. With the advantages of IP65 protection level, simple installation, strong anti-interference ability, it is no need to configure power supply and antenna; it can support the remote control, remote debugging, remote upgrading and other functions of the device, and can view the working status and power generation of the ...

Shenzhen Eybond Co., Ltd, established in 2014, is a high-tech enterprise specializing in technology research, product development and industrial application on internet+new energy. Based on rich industry experience and ...

Plug series pluggable datalogger can support GPRS and Wi-Fi. With the advantages of IP65 protection level, simple installation, strong anti-interference ability, it is no need to configure power supply and antenna; it can support the remote control, remote debugging, remote upgrading and other functions of the device, and can view the working status and power generation of the ...

Eybond Industrial control computer (hereinafter referred to as "industrial computer") and solar converter customized software, the software connects the slave device in the local area network through IEC104 protocol (master station), and establishes the local data logger link. Establish data transmission network with Eybond cloud and the third ...

Eybond Industrial control computer (hereinafter referred to as "industrial computer") and solar converter customized software, the software connects the slave device in the local area network through IEC104 protocol (master station), and establishes the local data logger link. ... Nanshan District, Shenzhen, China +86-755-89992588. Solutions ...



Shenzhen eybond co ltd Czechia

Eybond has rich experience in monitoring the energy IOT industry. You only need to raise the demand and leave the rest to us. At the same time, we have rich software products related to energy IOT industry. ... Building 10, Zhiheng Sicense & Technology Park, Nanshan District, Shenzhen, China +86-755-89992588. Solutions. WeChat. ShineMonitor.

Eybond has a deep photovoltaic background and rich experience in the Internet of things industry. It cooperates with inverter manufacturers to develop photovoltaic intelligent operation and maintenance solutions for different occasions. ... Nanshan District, Shenzhen, China +86-755-89992588. Solutions. WeChat. ShineMonitor.

Support Wi Fi, GPRS,4G, NB-IOT and other communication modes; Support RS-232, RS-485 serial port to communicate with device; Compatible with multi brand and multi type equipment (inverter, combiner box, environmental monitor, ammeter, etc.)

Eybond provide customers with diversified and multi scenario IOT terminal equipment to protect your IOT communication. According to the needs of customers, we will build a reliable, independent, secure and private software system through private cloud deployment solutions. ... Nanshan District, Shenzhen, China +86-755-89992588. Solutions ...

Magicbox Pro is one of the key device to build a centralized control center. It collects data of local device through RS-485, or obtains data of cloud server through Ethernet (RJ-45), Wi Fi and 4G, and displays monitoring data through display, projector, splicing screen, etc.

Dessmonitor optical energy storage management platform, based on the back-end server products of Eybond IOT cloud, provides users with application services such as data collection, analysis, calculation, storage, alarm push, ...

Shinemonitor System, based on the back-end server products of Eybond IOT cloud, provides users with application services such as power station management, equipment data acquisition, analysis, calculation, storage, alarm push, power station on-site video monitoring, etc. through advanced computing such as cloud computing, big data, intelligent sensor, etc. for the needs ...

With the continuous advancement of urban intelligence, energy-saving and environmental protection solar street lamps gradually replace the traditional street lamps cause of this, the safety maintenance, monitoring and management of solar street lamps in cities are essential view of the issues such as wide scattered street lights, poor real-time monitoring and difficult ...

Eybond is committed to the energy industry, developed by itself can be compatible with a variety of types of different brands of data collector and powerful control can treasure energy management system. Related equipment for real-time monitoring and control of the energy industry, has realized the remote online



Shenzhen eybond co ltd Czechia

monitoring of energy equipment ...

Gridbox is a device to prevent the electric energy from photovoltaic system from feeding into the public grid. It connects with the inverter through RS-485, uploads the data to the cloud server through wireless networks such as Wi-Fi, GPRS, 4G, etc. it can monitor the data of power generation, power consumption, power purchase in real time, support remote monitoring, set ...

Smartmeter series are intelligent terminal products of smart grid. It can support single-phase and three-phase modes. Equipped with standard RS-485 communication interface, it can be used with data logger to realize remote monitoring of data.

According to the characteristics of UPS, Eybond provides a variety of scenarios for UPS monitoring to ensure the normal operation of UPS. Wi-Fi Local(near field) Monitoring Scheme. ... Building 10, Zhiheng Sicense & Technology Park, Nanshan District, Shenzhen, China +86 ...

Web: <https://www.kindanewdecor.co.za>

